

easy-trim 

SPECIAL 1



WHATEVER, WEATHER

INSTALLATION GUIDANCE

The revolutionary flat roofing product available from

easy-trim 
Roofing & Construction Products

easy-trim SPECIAL 1

WHATEVER WEATHER

Easy-Trim Special 1 is a unique, single-component liquid waterproofing membrane that can be applied on wet and dry substrates.

Suitable for use on new roofs and existing membranes. It can also be used to waterproof balconies and terraces.

Features & Benefits:

- Can be applied on wet substrates
- Easy to install
- Can be used on existing membranes
- Quick curing
- Fully UV stable
- Certified for use without reinforcement
- Odourless & solvent free
- Isocyanate free
- Excellent adhesion
- Suitable for use on most substrates
- Resistant to standing water

The substrate should be sound and completely free of any dust, grease, oil, and debris.

Mix the product for 1 minute. This can be done by simply agitating the foil bag, or by pouring into the bucket.

The product can then be poured directly onto the substrate and spread using a roller or brush, adhering to consumption ratios.

The product can be applied to damp substrates and is self-levelling. (Any excess or standing water should be wiped away before application.)

The correct consumption ratio is 3KG per square metre.

Easy-Trim recommends using a reinforcement tape on any joints or seams, or substrate changes i.e. lips, steps, changes in direction etc.

Once opened, the liquid will be suitable for use for up to 2 weeks, if stored correctly in the tub with the lid on.

Large Scale Installations - Easy-Trim Special 1 has been fully tested to obtain W2 (minimum 10 Year life expectancy) without reinforcement. However, for large scale projects or installations where a longer life expectancy is required, a reinforcement can be used, and is recommended. Contact the Easy-Trim Technical Department for more advice.

For areas with high pedestrian traffic, we recommend coating the area with Easy-Trim EC-3 Hardwearing Layer. EC-3 should not be applied until Special-1 has fully cured.

Colour	Anthracite
Specific weight	1.40 ca g/ml
Skin Formation (20°C 50%UR)	40 minutes
Curing rate (20°C 50% UR)	2.5mm in 24 hours
Elongation at break	250%
Application temperature	+5°C at + 35°C
Operating Temperature	-30°C at +80°C

Limitations - Please ensure the correct consumption ratios are followed, failure to do so may result a system failure.

If working at lower temperatures, we recommend applying thinner coats to facilitate the curing process. The product can be recoated if necessary.

For installations where there is standing water, we recommend removing the excess water to avoid the brush or roller sliding out.

Storage - Store the product in its original packaging, in a dry place away from sunlight, at temperatures between +5 degrees to +25 degrees C. The stability of the product is 12 months from the date of manufacture when stored according to instructions.

Safety - For safety standards, please refer to the safety datasheet.

easy-trim 
Roofing & Construction Products

Tel 01282 930680
sales@easy-trim.co.uk
www.easy-trim.co.uk